

MATERIAL SAFETY DATA SHEET

Date Issued: 12/01/2008
 MSDS No: BS1010
 Date Revised: 06/11/2009
 Revision No: 2

Metal Primer

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Metal Primer
PRODUCT DESCRIPTION: Metal Primer
PRODUCT CODE: OT-ME
CHEMICAL FAMILY: Methacrylate
GENERIC NAME: Methyl Methacrylate

MANUFACTURER

Ortho Technology, Inc.
 17401 Commerce Park Boulevard
 Tampa FL 33647
Product Stewardship: 1-800-999-3161

24 HR. EMERGENCY TELEPHONE NUMBERS

For Chemical Emergency
 Spill Leak or Fire Exposure or Accident
 Call CHEMTREC Day or Night
 Domestic North America 1-800-424-9300
 International, Call +1 703-527-3887 (collect calls
 accepted)

2. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT(S)	CAS
Methacrylate Monomers	80-62-6

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Clear colorless liquid with fruity odor

POTENTIAL HEALTH EFFECTS

EYES: May cause irritation and burning.

SKIN: Can cause moderate irritation. Repeated exposure can cause allergic reaction.

INHALATION: Inhalation of vapor or mist can cause irritation of the nose and throat. Repeated or prolonged exposure can cause headache, nausea, drowsiness and unconsciousness.

MEDICAL CONDITIONS AGGRAVATED: Persons with pre-existing skin sensitivity.

ROUTES OF ENTRY: Inhalation, ingestion, skin contact.

4. FIRST AID MEASURES

EYES: Flush eyes with water for at least 15 minutes, lifting eyelids occasionally. Get medical attention immediately.

SKIN: Wash with soap and water for at least 15 minutes. remove any contaminated clothing.

INGESTION: If swallowed, dilute by giving 2 glasses of water to drink. Seek medical attention. Never give anything by mouth to an unconscious person.

MATERIAL SAFETY DATA SHEET

Date Issued: 12/01/2008
MSDS No: BS1010
Date Revised: 06/11/2009
Revision No: 2

Metal Primer

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. Call a physician.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: 10°C SETA Flash Tester CC

FLAMMABLE LIMITS: Not Established

EXTINGUISHING MEDIA: Chemical foam, Carbon dioxide, Dry chemicals, water spray

FIRE FIGHTING PROCEDURES: Fight advanced fires from a protected location. Use water spray to cool containers exposed to fire

FIRE EXPLOSION: Uncontrolled polymerization may produce a rapid release of energy with the potential for an explosion of unvented closed containers. Vapors are heavier than air and may travel to sources of ignition.

HAZARDOUS DECOMPOSITION PRODUCTS: None known.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Eliminate sources of ignition. Wear skin, eye and respiratory protection. Contain spills with inert material. Soak up liquid with absorbent material.

LARGE SPILL: Eliminate sources of ignition. Wear skin, eye and respiratory protection. Contain spills with inert material. Soak up liquid with absorbent material.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Material is highly volatile, keep containers tightly closed immediately after use.

HANDLING: Keep away from heat, sparks, flame, direct sunlight and elevated temperatures.

STORAGE: Keep away from heat, sparks, flame, direct sunlight and elevated temperatures.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Ventilation: Local exhaust strongly recommended.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Splash Goggles recommended.

SKIN: Disposable vinyl gloves recommended

RESPIRATORY: Use MSHA-NIOSH approved respirator for organic vapors.

PROTECTIVE CLOTHING: Chemical resistant apron.

WORK HYGIENIC PRACTICES: Normal safe practices. Use only in a highly professional manner.

OTHER USE PRECAUTIONS: Eyewash station

MATERIAL SAFETY DATA SHEET

Date Issued: 12/01/2008
MSDS No: BS1010
Date Revised: 06/11/2009
Revision No: 2

Metal Primer

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid
ODOR: Fruity odor
APPEARANCE: Clear colorless liquid.
COLOR: Colorless
VAPOR PRESSURE: Not Established
VAPOR DENSITY: Not Established
BOILING POINT: Not Established
MELTING POINT: Not Established
SOLUBILITY IN WATER: Moderately soluble
EVAPORATION RATE: (Butyl acetate = 1) Not Established
SPECIFIC GRAVITY: (H₂O = 1) 0.94

10. STABILITY AND REACTIVITY

STABILITY: Unstable.
POLYMERIZATION: Hazardous polymerization may occur.
CONDITIONS TO AVOID: Heat and sources of ignition.
POSSIBILITY OF HAZARDOUS REACTIONS: Polymerization catalyst may cause polymerization
HAZARDOUS DECOMPOSITION PRODUCTS: None known.
INCOMPATIBLE MATERIALS: Avoid contact with acids, bases, oxidizing agents, reducing agents, UV light

11. TOXICOLOGICAL INFORMATION

EYE EFFECTS: Irritation to the eyes can occur
SKIN EFFECTS: Irritation to the skin can occur
CARCINOGENICITY
IARC: Not Applicable
NTP: Not Applicable
OSHA: Not Applicable

12. ECOLOGICAL INFORMATION

MATERIAL SAFETY DATA SHEET

Date Issued: 12/01/2008
MSDS No: BS1010
Date Revised: 06/11/2009
Revision No: 2

Metal Primer

COMMENTS: Not Available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of waste in accordance with local, state, and federal regulations. Material is a hazardous waste (U162).

FOR LARGE SPILLS: Eliminate sources of ignition. Wear skin, eye and respiratory protection. Contain spills with inert material. Soak up liquid with absorbent material.

PRODUCT DISPOSAL: Dispose of waste in accordance with local, state, and federal regulations. Material is a hazardous waste (U162).

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Methyl methacrylate monomer, stabilized

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: UN1247

PACKING GROUP: II

LABEL: Flammable Liquid

AIR (ICAO/IATA)

SHIPPING NAME: Methyl methacrylate monomer, stabilized

UN/NA NUMBER: UN1247

PRIMARY HAZARD CLASS/DIVISION: 3

PACKING GROUP: II

LABEL: Flammable Liquid

COMMENTS: None required

15. REGULATORY INFORMATION

COMMENTS None Reported

16. OTHER INFORMATION

REASON FOR ISSUE: New MSDS Format

APPROVED BY: J. Hutchins **TITLE:** QA/RA Director

PREPARED BY: T. Swan

INFORMATION CONTACT: 1-800-999-3161

REVISION SUMMARY: Revision #: 2. This MSDS replaces the June 09, 2009 MSDS. Any changes in


MATERIAL SAFETY DATA SHEET

Date Issued: 12/01/2008
MSDS No: BS1010
Date Revised: 06/11/2009
Revision No: 2

Metal Primer

information are as follows: In Section 1: 24 Hour Emergency Phone Numbers

NFPA CODES



MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.