

# SAFETY DATA SHEET

Date Issued: 12/18/2008

MSDS No: BS1003B

## Resilience®Liquid Etch

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**PRODUCT NAME:** Resilience®Liquid Etch  
**PRODUCT DESCRIPTION:** Green Liquid Etchant  
**PRODUCT CODE:** 506107; 503204  
**CHEMICAL FAMILY:** Phosphoric Acid  
**GENERIC NAME:** Phosphoric Acid

#### MANUFACTURER

Ortho Technology, Inc.  
 17401 Commerce Park Boulevard  
 Tampa FL 33647  
**Product Stewardship:** 1-800-999-3161

**COMMENTS:** This product may be a component of the Following Item Numbers: FC-RESI-047, FC-RESI-048 and FC-RESI-049

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS	EINECS	Classification	Content
Phosphoric Acid - 37%	7664-38-2	231-633-2	R22, R34, S24, S25, S26, S28, S36, S39, S46	~ 37

( Full text of R-Phrases can be found under heading 16 )

### 3. HAZARDS IDENTIFICATION

#### HAZARD DESIGNATION

"C" - Corrosive

#### EMERGENCY OVERVIEW

**PHYSICAL APPEARANCE:** Green-colored Liquid

#### POTENTIAL HEALTH EFFECTS

**EYES:** Mild to severe irritant

**SKIN:** Mild to severe irritant

**INGESTION:** Slightly toxic

**INHALATION:** Severe irritant

### 4. FIRST AID MEASURES

**EYES:** Flush with copious amounts of water for at least 15 minutes. Seek medical attention.

**SKIN:** Wash with soap and water for at least 15 minutes.

**INGESTION:** Do not induce vomiting. Wash out mouth with water, keep at rest.

# SAFETY DATA SHEET

Date Issued: 12/18/2008

MSDS No: BS1003B

## Resilience®Liquid Etch

**INHALATION:** Remove person to fresh air.

### 5. FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Material is not flammable.

**EXPLOSION HAZARDS:** None Reported

**FIRE FIGHTING PROCEDURES:** None required

**FIRE FIGHTING EQUIPMENT:** Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Emits toxic fumes of oxides of phosphorus.

### 6. ACCIDENTAL RELEASE MEASURES

#### ENVIRONMENTAL PRECAUTIONS

**WATER SPILL:** May cause adverse environmental impact if material reaches waterways

**GENERAL PROCEDURES:** Cover with sodium carbonate and calcium hydroxide. Collect material. Place in an approved metal container.

**SPECIAL PROTECTIVE EQUIPMENT:** Glove and eye protection suggested

### 7. HANDLING AND STORAGE

**HANDLING:** To be handled by qualified dental professionals. Follow instructions for use.

**STORAGE:** Store at or below room temperature. Avoid moisture in unpolymerized state. Do not expose to any light.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Safety glasses or splash goggles

**SKIN:** Lab coat and gloves

**RESPIRATORY:** Respiratory protection is recommended when using large amounts

**PROTECTIVE CLOTHING:** Lab Coat.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**FLASHPOINT AND METHOD:** Non Flammable

**AUTOIGNITION TEMPERATURE:** No data

**PHYSICAL STATE:** Liquid

**ODOR:** No Obvious Odor.

**APPEARANCE:** Viscous liquid

# SAFETY DATA SHEET

Date Issued: 12/18/2008

MSDS No: BS1003B

## Resilience®Liquid Etch

**COLOR:** Green

**BOILING POINT:** No data

**MELTING POINT:** No Data

**SOLUBILITY IN WATER:** Soluble

**SPECIFIC GRAVITY:** 1.3

### 10. STABILITY AND REACTIVITY

**STABILITY:** Stable.

**POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID:** Avoid dehydration, Keep container closed.

**POSSIBILITY OF HAZARDOUS REACTIONS:** None reported

**HAZARDOUS DECOMPOSITION PRODUCTS:** At flame temperatures, material will emit toxic phosphorus oxide fumes

**INCOMPATIBLE MATERIALS:** Reactive metals and bases are materials to be avoided.

### 11. TOXICOLOGICAL INFORMATION

#### ACUTE

**ORAL LD<sub>50</sub>:** 1530 mg/kg (for 85% phosphoric acid)

**EYE EFFECTS:** Irritation to the eyes can occur

**SKIN EFFECTS:** Irritation to the skin can occur

### 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** May cause adverse environmental impact if material reaches waterways

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Dispose of waste at an appropriate waste disposal facility according to current applicable laws and regulations

### 14. TRANSPORT INFORMATION

### 15. REGULATORY INFORMATION

#### EUROPEAN COMMUNITY

# SAFETY DATA SHEET

Date Issued: 12/18/2008

MSDS No: BS1003B

## Resilience®Liquid Etch

### EEC LABEL SYMBOL AND CLASSIFICATION



"C" - Corrosive

### 16. OTHER INFORMATION

#### RELEVANT R-PHRASES:

R22: Harmful if swallowed.

R34: Causes burns.

S24: Avoid contact with skin.

S25: Avoid contact with eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28: After contact with skin, wash immediately with plenty of water and soap.

S36: Wear suitable protective clothing.

S39: Wear eye/face protection.

S46: If swallowed, seek medical advice immediately and show this container or label.

**REASON FOR ISSUE:** New MSDS Format**APPROVED BY:** J. Hutchins    **TITLE:** QA/RA DIrector**PREPARED BY:** T. Swan**INFORMATION CONTACT:** 1-800-999-3161**REVISION SUMMARY:** New MSDS

**MANUFACTURER DISCLAIMER:** To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.