

# MATERIAL SAFETY DATA SHEET

Date Issued: 12/18/2008

MSDS No: BS1003A

## Resilience® Gel Etchant

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Resilience® Gel Etchant  
**PRODUCT DESCRIPTION:** Green Etchant Gel  
**PRODUCT CODE:** 501009;503202;506101;506102;506104;506106  
**CHEMICAL FAMILY:** Phosphoric Acid  
**GENERIC NAME:** Phosphoric Acid

#### MANUFACTURER

Ortho Technology, Inc.  
 17401 Commerce Park Boulevard  
 Tampa FL 33647  
**Product Stewardship:** 1-800-999-3161

**COMMENTS:** This product may be a component of the Following Item Numbers: FC-RESI-006, FC-RESI-007 and FC-RESI-012

### 2. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

**PHYSICAL APPEARANCE:** Green colored gel

#### POTENTIAL HEALTH EFFECTS

**SKIN:** Mild to severe irritant  
**INGESTION:** Slightly toxic  
**INHALATION:** Severe irritant

#### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**SKIN:** Repeated contact with skin may lead to burns and rashes.  
**ACUTE TOXICITY:** Slightly Toxic When Inhaled or Ingested.  
**CHRONIC EFFECTS:** Slightly Toxic When Repeated Inhalation or Ingestion.

**MEDICAL CONDITIONS AGGRAVATED:** Unknown

**ROUTES OF ENTRY:** Inhalation, Ingestion, and Skin.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Vol. %	CAS
Phosphoric Acid - 37%	37	7664-38-2

### 4. FIRST AID MEASURES

**EYES:** Flush with copious amounts of water for at least 15 minutes.

**SKIN:** Wash with soap and water for at least 15 minutes.

# MATERIAL SAFETY DATA SHEET

Date Issued: 12/18/2008

MSDS No: BS1003A

## Resilience® Gel Etchant

**INGESTION:** Do not induce vomiting. Drink Copious Amounts of Water.

**INHALATION:** Remove from Exposure.

### 5. FIRE FIGHTING MEASURES

**FLAMMABLE LIMITS:** N/A to N/A

**FLAMMABLE CLASS:** Material is not flammable.

**EXTINGUISHING MEDIA:** NA = Not Applicable

**FIRE FIGHTING PROCEDURES:** Use full protective clothing and self contained breathing apparatus.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Will emit toxic Phosphorous Oxide fumes.

### 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Cover with sodium carbonate and calcium hydroxide. Collect material. Place in an approved metal container.

#### ENVIRONMENTAL PRECAUTIONS

**WATER SPILL:** May cause adverse environmental impact if material reaches waterways

**GENERAL PROCEDURES:** For industrial or professional use only. Please see package insert for additional precautionary warnings.

### 7. HANDLING AND STORAGE

**HANDLING:** To be handled by qualified dental professionals.

**STORAGE TEMPERATURE:** Store at or below room temperature. Keep container dry. Keep container in well-ventilated area.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Ventilation : Local Exhaust is recommended.

#### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Safety glasses or splash goggles

**SKIN:** Gloves recommended.

**RESPIRATORY:** Respiratory Protection Recommended

**PROTECTIVE CLOTHING:** Wear lab coat

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Viscous gel

**ODOR:** Odorless

# MATERIAL SAFETY DATA SHEET

Date Issued: 12/18/2008

MSDS No: BS1003A

## Resilience® Gel Etchant

**COLOR:** Green

**VAPOR PRESSURE:** ND = No Data/Not Determined

**VAPOR DENSITY:** ND = No Data/Not Determined

**BOILING POINT:** ND = No Data/Not Determined

**MELTING POINT:** ND = No Data/Not Determined

**SOLUBILITY IN WATER:** Soluble

**EVAPORATION RATE:** (Butyl acetate = 1) ND = No Data/Not Determined

**SPECIFIC GRAVITY:** (H<sub>2</sub>O = 1) 1.3

### 10. STABILITY AND REACTIVITY

**STABILITY:** Stable.

**POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID:** Avoid dehydration, Keep container closed.

**HAZARDOUS DECOMPOSITION PRODUCTS:** At flame temperatures, material will emit toxic phosphorus oxide fumes

**INCOMPATIBLE MATERIALS:** Reactive Metals and Bases.

### 11. TOXICOLOGICAL INFORMATION

#### ACUTE

**ORAL LD<sub>50</sub>:** 1530 mg/kg (for 85% phosphoric acid)

**EYE EFFECTS:** Irritation to the eyes can occur

**SKIN EFFECTS:** Irritation to the skin can occur

### 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** May cause adverse environmental impact if material reaches waterways

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Dispose of in accordance with Federal, State, and Local Regulations.

### 14. TRANSPORT INFORMATION

#### DOT (DEPARTMENT OF TRANSPORTATION)

**PRIMARY HAZARD CLASS/DIVISION:** 8

**UN/NA NUMBER:** UN 1805

# MATERIAL SAFETY DATA SHEET

Date Issued: 12/18/2008

MSDS No: BS1003A

## Resilience® Gel Etchant

---

**PACKING GROUP:** III**OTHER SHIPPING INFORMATION:** Corrosive Material**ROAD AND RAIL (ADR/RID)****UN NUMBER:** UN 1805**HAZARD CLASS:** 8**PACKING GROUP:** III**NOTE:** Corrosive Material**AIR (ICAO/IATA)****UN/NA NUMBER:** UN 1805**PRIMARY HAZARD CLASS/DIVISION:** 8**PACKING GROUP:** III**NOTE:** Corrosive Material**VESSEL (IMO/IMDG)****UN/NA NUMBER:** UN 1805**PRIMARY HAZARD CLASS/DIVISION:** 8**PACKING GROUP:** III**NOTE:** Corrosive Material**CANADA TRANSPORT OF DANGEROUS GOODS****UN/NA NUMBER:** UN 1805**PRIMARY HAZARD CLASS/DIVISION:** 8**PACKING GROUP:** III**TDG NOTE:** Corrosive Material**15. REGULATORY INFORMATION****16. OTHER INFORMATION****REASON FOR ISSUE:** New MSDS Format**APPROVED BY:** J. Hutchins     **TITLE:** QA/RA Director**PREPARED BY:** T. Swan**INFORMATION CONTACT:** 1-800-999-3161**REVISION SUMMARY:** New MSDS

**MANUFACTURER DISCLAIMER:** To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

# MATERIAL SAFETY DATA SHEET

Date Issued: 12/18/2008  
MSDS No: BS1003A

**Resilience® Gel Etchant**

---