

SAFETY DATA SHEET

Date Issued : 06/12/2013
MSDS No : BS1003B
Date Revised : 11/03/2015
Revision No : 5

Resilience®Liquid Etch

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Resilience®Liquid Etch
PRODUCT DESCRIPTION: 6903M7C7
PRODUCT CODE: 506107; 503204
CHEMICAL FAMILY: Phosphoric Acid
GENERIC NAME: Phosphoric Acid

MANUFACTURER

Ortho Technology, Inc.
17401 Commerce Park Boulevard
Tampa, FL 33647
Emergency Phone: 1-800-999-3161
E-Mail: ljohnson@orthotechnology.com

COMMENTS: This product may be a component of the Following Item Numbers: FC-RESI-047, FC-RESI-048 and FC-RESI-049

2. HAZARDS IDENTIFICATION

GHS LABEL

Irritating to skin



Exclamation
mark

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H314: Causes severe skin burns and eye damage.
H302 + H332: Harmful if swallowed or if inhaled.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Green-colored Liquid

POTENTIAL HEALTH EFFECTS

EYES: Mild to severe irritant

SKIN: Mild to severe irritant

INGESTION: Slightly toxic

INHALATION: Severe irritant

3. COMPOSITION / INFORMATION ON INGREDIENTS

SAFETY DATA SHEET

Date Issued : 06/12/2013
MSDS No : BS1003B
Date Revised : 11/03/2015
Revision No : 5

Resilience®Liquid Etch

INGREDIENT(S)	CAS	Vol. %
Phosphoric Acid - 37%	7664-38-2	15 - 40
Polyvinyl alcohol	25213-24-5	< 0.1 - 1

4. FIRST AID MEASURES

EYES: Flush with copious amounts of water for at least 15 minutes. Seek medical attention.

SKIN: Wash with soap and water for at least 15 minutes.

INGESTION: Do not induce vomiting. Wash out mouth with water, keep at rest.

INHALATION: Remove person to fresh air.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Material is not flammable.

EXPLOSION HAZARDS: None Reported

FIRE FIGHTING PROCEDURES: None required

FIRE FIGHTING EQUIPMENT: Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus.

HAZARDOUS DECOMPOSITION PRODUCTS: Emits toxic fumes of oxides of phosphorus.

6. ACCIDENTAL RELEASE MEASURES

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: May cause adverse environmental impact if material reaches waterways

GENERAL PROCEDURES: Cover with sodium carbonate and calcium hydroxide. Collect material. Place in an approved metal container.

SPECIAL PROTECTIVE EQUIPMENT: Glove and eye protection suggested

7. HANDLING AND STORAGE

HANDLING: To be handled by qualified dental professionals. Follow instructions for use.

STORAGE: Store at or below room temperature. Avoid moisture in unpolymerized state. Do not expose to any light.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety glasses or splash goggles

SKIN: Lab coat and gloves

RESPIRATORY: Respiratory protection is recommended when using large amounts

PROTECTIVE CLOTHING: Lab Coat.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

SAFETY DATA SHEET

Date Issued : 06/12/2013
MSDS No : BS1003B
Date Revised : 11/03/2015
Revision No : 5

Resilience®Liquid Etch

ODOR: No Obvious Odor.
APPEARANCE: Viscous liquid
COLOR: Green
FLASHPOINT AND METHOD: Non Flammable
AUTOIGNITION TEMPERATURE: No data
BOILING POINT: No data
MELTING POINT: No Data
SOLUBILITY IN WATER: Soluble
SPECIFIC GRAVITY: 1.3

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Will not occur.
STABILITY: Stable.
CONDITIONS TO AVOID: Avoid dehydration, Keep container closed.
POSSIBILITY OF HAZARDOUS REACTIONS: None reported
HAZARDOUS DECOMPOSITION PRODUCTS: At flame temperatures, material will emit toxic phosphorus oxide fumes
INCOMPATIBLE MATERIALS: Reactive metals and bases are materials to be avoided.

11. TOXICOLOGICAL INFORMATION

ACUTE
ORAL LD₅₀: 1530 mg/kg (for 85% phosphoric acid)
EYE EFFECTS: Irritation to the eyes can occur
SKIN EFFECTS: Irritation to the skin can occur

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: May cause adverse environmental impact if material reaches waterways

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of waste at an appropriate waste disposal facility according to current applicable laws and regulations

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)
PROPER SHIPPING NAME: Phosphoric Acid Solution
PRIMARY HAZARD CLASS/DIVISION: 8
UN/NA NUMBER: UN1805
PACKING GROUP: III
LABEL: Corrosive Material

SAFETY DATA SHEET

Date Issued : 06/12/2013
MSDS No : BS1003B
Date Revised : 11/03/2015
Revision No : 5

Resilience®Liquid Etch

OTHER SHIPPING INFORMATION: Corrosive Material

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION



Corrosive

CANADA

WHMIS HAZARD SYMBOL AND CLASSIFICATION



Corrosive

16. OTHER INFORMATION

REASON FOR ISSUE: New MSDS Format

APPROVED BY: J. Hutchins **TITLE:** QA/RA Director

PREPARED BY: T. Swan

INFORMATION CONTACT: 1-800-999-3161

REVISION SUMMARY: This MSDS replaces the 03/19/2014 MSDS. Revised: **Section 1:** REASON FOR ISSUE. **Section 2:** . **Section 3:** Wt.%.

MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.