

SAFETY DATA SHEET

WORKING COPY

Date Prepared : 02/18/2009
MSDS No : BS1028

Resilience® Low Viscosity Light-Cure Flowable Composite

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Resilience® Low Viscosity Light-Cure Flowable Composite
PRODUCT DESCRIPTION: 6763M69B
PRODUCT CODE: FC-RESI-007/ FC-RESI-008
CHEMICAL FAMILY: Aromatic and Aliphatic Dimethacrylate Monomers
GENERIC NAME: Orthodontic Adhesive

MANUFACTURER

Ortho Technology, Inc.
 17401 Commerce Park Boulevard
 Tampa, FL 33647
Emergency Phone: 1-800-999-3161
E-Mail: ljohnson@orthotechnology.com

2. HAZARDS IDENTIFICATION

GHS LABEL

Irritating to skin



Exclamation
mark

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H316: Causes mild skin irritation.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Resin

POTENTIAL HEALTH EFFECTS

SKIN: Repeated Exposure to Skin May Cause Irritation and Reddening.

CARCINOGENICITY: ND = No Data/Not Determined

ROUTES OF ENTRY: Inhalation - Not Determined

Skin - Yes

Ingestion - Possible

HEALTH HAZARDS: ND = No Data/Not Determined

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
Bisphenol "A" Diglycidyl Methacrylate	~ 0 - 100	156-94-2
N-N Dihydroxyethyl P-Toluidine	~ 0 - 100	3077-12-1

4. FIRST AID MEASURES

SAFETY DATA SHEET

WORKING COPY

Date Prepared : 02/18/2009

MSDS No : BS1028

Resilience® Low Viscosity Light-Cure Flowable Composite

EYES: Flush eye with copious amounts of water.

SKIN: Wash with soap and water.

INGESTION: Seek medical attention

INHALATION: ND = No Data/Not Determined

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry Chemical Foam, CO₂, Dry Chemical

FIRE FIGHTING EQUIPMENT: Firefighters should wear full protective clothing and self-contained breathing apparatus.

FIRE EXPLOSION: Material may burn if exposed to flame

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Collect Spilled Materials

7. HANDLING AND STORAGE

STORAGE: Store at or below room temperature.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: None required

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Eye protection recommended

SKIN: Gloves recommended.

RESPIRATORY: None

PROTECTIVE CLOTHING: None

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Filled Resin

ODOR: Characteristic acrylate odor

APPEARANCE: Resin

FLASHPOINT AND METHOD: ND = No Data/Not Determined

FLAMMABLE LIMITS: ND = No Data/Not Determined

VAPOR PRESSURE: ND = No Data/Not Determined

VAPOR DENSITY: ND = No Data/Not Determined

BOILING POINT: ND = No Data/Not Determined

MELTING POINT: ND = No Data/Not Determined

SOLUBILITY IN WATER: Insoluble.

EVAPORATION RATE: (Butyl acetate = 1) ND = No Data/Not Determined

SPECIFIC GRAVITY: (H₂O=1) 1.6

SAFETY DATA SHEET

WORKING COPY

Date Prepared : 02/18/2009
MSDS No : BS1028

Resilience® Low Viscosity Light-Cure Flowable Composite

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Hazardous polymerization may occur in large quantities.

STABILITY: Stable.

CONDITIONS TO AVOID: High Temperatures. Exposure to Any Visible Light Sources.

HAZARDOUS DECOMPOSITION PRODUCTS: ND = No Data/Not Determined

INCOMPATIBLE MATERIALS: Strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

CARCINOGENICITY

Notes: ND = No Data/Not Determined

12. ECOLOGICAL INFORMATION

COMMENTS: ND = No Data/Not Determined

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose in accordance with local, state, and federal regulations.

14. TRANSPORT INFORMATION

COMMENTS: None Reported

15. REGULATORY INFORMATION

COMMENTS None Reported

16. OTHER INFORMATION

REASON FOR ISSUE: New MSDS Format

APPROVED BY: QA/RA Director

PREPARED BY: QA Specialist **Date Prepared:** 02/18/2009

INFORMATION CONTACT: 1-800-999-3161

MANUFACTURER DISCLAIMER: The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Ortho Technology assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by this material. Such vendees or users assume all risks associated with the use of the material.